



EF10.2

- Screw connection
- Mounting flange position 2
- 21-22 (Contact labelling)

Data

Ordering data

Product type description	EF10.2
Article number (order number)	101006536
EAN (European Article Number)	4250116201129
eCl@ss number, version 12.0	27-37-13-02
eCl@ss number, version 11.0	27-37-13-02
eCl@ss number, version 9.0	27-37-13-02
ETIM number, version 7.0	EC000041
ETIM number, version 6.0	EC000041

Approvals - Standards

Certificates	cULus
--------------	-------

General data

Standards	EN IEC 60947-5-1 EN IEC 60947-1
Versions	Contact element
Design	Slow action

Housing material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Gross weight	19 g

General data - Features

Number of normally closed (NC)	1
--------------------------------	---

Mechanical data

Installation instructions	pluggable
Mechanical life, minimum	10,000,000 Operations
Positive break travel	2 mm
Contact opening	1 mm
Note Bounce duration	Bounce duration at an Actuating speed of 100mm/s
Mounting flange position	1

Mechanical data - Connection technique

Termination	Screw terminals
Cable section, minimum	0.5 mm ² , rigid 0.5 mm ² , flexible
Cable section, maximum	2.5 mm ² , rigid 1.5 mm ² , flexible
Note	All indications including the conductor ferrules.

Mechanical data - Dimensions

Length	46 mm
Width	10 mm
Depth	60 mm

Ambient conditions

Degree of protection of the switch rooms	IP40
Degree of protection of clips or terminals	IP20

Ambient temperature	-25 ... +80 °C
Restistance to shock	110 g / 4 ms
Resistant to vibration	Resistance to vibration: 20 g / 10...200 Hz

Ambient conditions - Insulation values

Rated insulation voltage U_i	400 V
--------------------------------	-------

Electrical data

Thermal test current	10 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	8 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	5 A
Suitable for low-voltages	$\geq 5 \text{ V} / \geq 3.2 \text{ mA}$
Switching element	Opener (NC)
Switching principle	Slow action
Bounce duration, maximum	5 ms
Maximum switching frequency	1,200 /h
Material of the contacts, electrical	Silver
Contact labelling	21-22


Pictures

Product picture (catalogue individual photo)



ID: kef03f-blanko
 | 286.5 kB | .jpg | 352.778 x 352.778 mm - 1000 x 1000 px - 72 dpi
 | 35.5 kB | .png | 74.083 x 74.083 mm - 210 x 210 px - 72 dpi
 | 46.3 kB | .jpg | 123.472 x 123.472 mm - 350 x 350 px - 72 dpi

Switch travel diagram




ID: krf--s01

| 18.5 kB | .cdr |

| 1,020.0 b | .png | 74.083 x 16.933 mm - 210 x 48 px - 72 dpi

| 19.6 kB | .jpg | 352.778 x 80.433 mm - 1000 x 228 px - 72 dpi

Operating principle



ID: krf--a05

| 19.5 kB | .cdr |

| 189.7 kB | .jpg | 352.778 x 711.2 mm - 1000 x 2016 px - 72 dpi

| 3.7 kB | .png | 74.083 x 149.225 mm - 210 x 423 px - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, 42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 13/01/2025, 10:34