


# DNS CABLE CAT6 UTP UV-PE 400104

- EC Verified
- 100% tested acc. to ISO/IEC 11801; EN 50173-1; ANSI/TIA-568-C
- 25 Year DNS Warranty
- RoHS Compliant



## FEATURES

- 25 year DNS Warranty
- Rip Cord
- Central `X` Filler
- 23AWG conductor
- 305m Box
- UVHD-PE Black Outer Sheath
- 100% tested acc. to ISO/IEC 11801; EN 50173-1

## CONSTRUCTION

Outer Diameter(±0.3mm)	6.1mm
Jacket Nom. Thickness	UVHD-PE 0.65mm
Conductor	Solid Bare Copper AWG23
Installation Temperature Range	-10 to +60°C
Operating Temperature Range	-40 to +60°C
Minimum Bend Radius	4x overall diameter installed, 8x during installation
Cable Weight	4,9 Kg/100m
305m Box Weight	15 Kg (inc. box)
Box Dimensions	246mm wide x 415mm high x 420mm deep

## PERFORMANCE OVERVIEW

Category 6 cables are manufactured and tested to the Category 6 performance standards defined by the TIA, ISO and EN standards bodies. Actual performance far exceeds the required standard.

The cable is also compatible with Category 5 and 5e components.

## PERFORMANCE TEST DATA

Freq MHz	NEXT (dB)	ATT(dB)	RL (dB)	PS NEXT (dB)	ELFEXT (dB)	PS ELFEXT (dB)
	DNS	DNS	DNS	DNS	DNS	DNS
1	82.5	2.0	21.0	80.4	75.7	72.6
10	66.9	5.8	27.0	64.8	54.9	51.8
16	63.7	7.4	27.0	61.7	50.7	47.5
20	62.2	8.3	27.0	60.2	48.6	45.5
25	60.7	9.3	25.9	58.6	46.6	43.5
31.25	59.2	10.4	25.7	57.1	44.6	41.5
62.5	54.5	15.1	23.7	52.4	38.3	35.2
100	51.3	19.3	23.5	49.2	34.1	31.0
200	49.6	28.2	23.0	44.6	27.8	24.7
250	29.3	39.5	16.3	26.3	13.8	12.8

## TYPICAL APPLICATIONS

- 1000BASE-T Gigabit Ethernet
- 10GBase UP to 55m\*
- LAN networks
- Audio
- 100BASE-TX Ethernet
- Horizontal cabling
- Telephone
- Video

\*DNS Cat6 UTP perform in non hostile Alien Crosstalk environment up to 55m, but in hostail(lot of cables bundeled together) Alien Crosstalk environment DNS cat6 UTP perform up to 37m.

## DNS WARRANTY SYSTEM

The DNS System Warranty provides a 25-year product and applications warranty. The guarantee cover system and application performance according to EN50173-1:2002, ANSI/TIA/EIA-568-B.2:2002 and ISO/IEC 11801-2 at the time of proper signed application form. The warranty may be applied by the certified DNS Partner.