




Smart DALI Converter

- NEW: Wireless communication based on future-proof, standardized Bluetooth SIG Mesh protocol
- Compact BLE to DALI converter for use in OPple Smart Lighting System
- Integrate any brand of DALI luminaire into the OPple Smart Lighting System
- Control of up to 64 DALI luminaires with Smart Switch or Smart App (DALI Broadcast commands, including Tunable White control of DALI DT8 luminaires)
- Compatible with OPple BLE2 Smart Sensors & OPple BLE2 Smart Switch
- Very easy to set up with the OPple Smart Lighting App, or Smart Connect Box through the web user interface
- Including built-in energy meter, to read out in the app or web user interface
- Complete wireless communication via standardized Bluetooth® Low Energy (BLE) SIG Mesh protocol



Specifications

| Item Code | Item Description |
|--------------|------------------------------|
| 821017003200 | LEDSmart-BLE2-DALI-Converter |

| Technical Specifications | |
|------------------------------|--|
| IP-class | IP20 |
| Protection | II |
| Finishing | White RAL9003 |
| Communication | Opple Bluetooth® Low Energy Mesh (BLE2) |
| Dimming method | DALI Broadcast (DT8) |
| Integrated DALI power supply | Yes |


| Electrical Supply | |
|-------------------|---------------------|
| Nominal voltage | 220-240 V AC |
| Frequency | 50 Hz |
| Connection cable | 0.75mm ² |
| Cable Length | 12 cm |



| Mechanical Properties | |
|-----------------------|----|
| Material housing | PC |

| Ambient conditions | |
|-------------------------|-----------|
| Application Temperature | +25°C |
| Operating Temperature | -20-+45°C |

Dimensional drawing (mm)



821017003200 - LEDSmart-BLE2-DALI-Converter

